

LUBECHEM ANTIFREEZE G12 +

Antifreeze on base of ethylene glycol- OAT



Data Sheet

Description

Antifreeze on base of ethylene glycol, free from phosphate, nitrite and amines with high protection against freezing, overheating, corrosion and cavitation. **Lubechem Antifreeze G12+** is especially suitable for all requirements of aluminum and casting. It protects safety from foaming

Application

LUBECHEM ANTIFREEZE G12+ is **33% - 40% - 50%** (ready Mix) used in cooling systems of new passenger cars and CNC machines.

33% proportion of antifreeze down to -18°C 40% proportion of antifreeze down to -25°C 50% anti-freeze to -38°C

Qualification

ASTM D1384, D2870, D3306, D4340	SAE J1034
AS 2108-2004	BS 6580 (2010)
DAF 74002	MAN 324 SNF
PN-C-40007	Ford WSS-M97B44-D (2013)
GM 6277M	GMW3420 (2012)
UNE 26-361-88 VW TL 774 Type D/F (2014)	ONORM V 5123 (2009)
	JIS K 2234 (2006)
	MB 325.3

Technical Data

Color	red
Density 20°C	DIN 51757 1,16 g/cm ³
pH 20°C	ASTM D1287 7,7 - 8,5

* Approval by name of the manufacturer

To the best of our knowledge, all information in this product information is based on the current state of knowledge. We reserve the right to make changes. Given the variety of possible applications and conditions of use by users, our application instructions can only be general. They cannot be transferred to each individual case and are non-binding. Our general terms and conditions of sale and delivery apply exclusively to liability regulations.

ISO 9001 and 14001 certified

Stand 05.03.2022

